

93315

Cold water hose, 1/2"(Q),
10000 mm, White



This hose is ideal for cleaning with water up to 40° C. It is equipped with a 1/2" Q-coupling in both hose ends. Water tap nipple, 0700 provided for 1/2", 3/4" and M22x1 screw thread types. Can be used with the following Vikan Q-couplings 0700, 0705 and 0712 as well as other Vikan products equipped with a 1/2" Q-nipple.

Technical Data

Item Number	93315
Couplings Size	1/2 "
Hose Length	10000 mm
Material	PVC Chromium-plated brass Polyester
Complies with (EC) 1935/2004 on food contact materials ¹	No
FDA compliant raw material (CFR 21)	No
Complies with UK 2019 No. 704 on food contact materials	No
Meets the REACH Regulation (EC) No. 1907/2006	Yes **
California Proposition 65 Compliant	No
SCIP number	e076bd6a-4e68-4749- b630-d5209d74b654
Use of phthalates and bisphenol A	No
Is Halal and Kosher compliant	Yes
Box Quantity	1 Pcs.
Quantity per Pallet (80 x 120 x 180-200 cm)	231 Pcs
Quantity Per Layer (Pallet)	1 Pcs.
Length	275 mm
Width	260 mm
Height	125 mm
Net Weight	1.7 kg
Weight cardboard (Recycling symbol "20" PAP)	0 kg
Tare total	0 kg
Gross Weight	1.7 kg
Cubik metre	0.008938 M3
Max. cleaning temperature (Dishwasher)	40 °C
Max usage temperature (non food contact)	40 °C
Min. usage temperature ³	-5 °C
Min. pH-value in usage concentration	2 pH
Max. pH-value in Usage Concentration	11 pH
Max. bars pressure	12 Bar
Gtin-13 Number	5705020933158
Customs Tariff No.	39173300
Country of origin	Italy

The hose coupling on the hose and foaming gun have to be greased regularly to maintain the coupling ability on the equipment. The grease applied during mounting will be rinsed away by the water flow and thus needs to be renewed.

** Lead (Pb, CAS: 7439-92-1) is on the REACH candidate list as a Substance of Very High Concern (SVHC). This product contains lead (Pb) in a concentration above 0.1% w/w. Consequently the REACH Regulation (EC) No. 1907/2006 require Vikan to notify our customers of the content of lead. This product is registered in the EU SCIP database. Please find SCIP number above.