

Heavy Duty Scraper

→ ENTRANCE MAT • OUTDOOR




→ WHY CHOOSE THIS MAT?

Tufted cut pile manufactured with twisted and heat set BCF polyamide 6 monofilaments on rubber backing.

- **Exceptional Durability** – Built to withstand heavy foot traffic and harsh outdoor conditions, providing long-lasting performance
- **Effective Debris Removal** – The tufted cut pile design efficiently scrapes off dirt, mud, and debris from shoes, helping to keep your space clean
- **All-Weather Reliability** – Designed for outdoor use, these mats resist the elements with their rubber backing and weather-resistant construction
- **Recycled Materials** – Made with 100% Econyl regenerated BCF polyamide, these mats contribute to sustainability efforts while maintaining top-tier performance
- **Slip-Resistant** – The rubber backing not only keeps the mat in place but also enhances safety by preventing slips and trips
- **Low Maintenance** – With its heavy-duty construction, these mats require minimal upkeep, saving you time and effort
- **Stylish and Functional** – Combining durability with a sleek design, the Heavy Duty Scraper™ mat enhances the aesthetics of your entrance while serving its practical purpose
- There is **34% postindustrial recycled content** in the rubber polymer

→ SPECIFICATIONS

Material	100% Econyl ® regenerated BCF polyamide twisted and heat set monofilaments • Carpet weight: 780 gr/m²
Backing	• Rubber backing: 100% nitrile rubber for maximum oil resistance, durability, and performance. Compression-molded with reinforced borders on all four sides. There is 34% post industrial recycled content in the polymer.
Other properties	• Total weight: 2880 gr/m²
Safety	• Flammability: EN13501-1 (2024) Fire Certificate
Colour	Grey



→ STANDARD SIZES

85 x 150 85 x 300 115 x 200

Size Tolerance: +/- 2%

→ CLEANING INSTRUCTIONS



Heavy Duty Scraper mats can be cleaned in several different ways:

1. They can be commercially laundered (see Laundering Instructions)
2. Vacuumed regularly (daily in high-traffic areas; weekly in lower-traffic applications)
3. Cleaned with an extractor and laid flat to dry

Hang to dry. Mats should always be dry before they are placed back in service and cooled before rolling.

Laundering Instructions

1. Flush, 2-3 Min. on a medium water level with a maximum temperature of 49°C
2. Flush (optional), 2-3 Min. on a medium water level with a maximum temperature of 49 °C
3. Break, 2-3 Min. on a high water level with a maximum temperature of 49 °C
4. Rinse, 2 Min. on a high water level with cold temperature
5. Rinse, 2 Min. on a high water level with cold temperature
6. Extract on low speed, 1-2 Min.
7. Shakeout with the drum turning, 1 Min.
8. Extract, on a maximum of 250G, 3-5 Min.
9. Dry (optional), 5-10 Min. with a maximum basket temperature of 82 °C
10. Cooldown, 5 Min.

Additional recommendations

- All Solution Dyed Mats can be washed together.
- For Heavy Soiled Mats, increase the temperature up to max. 71 °C.
- The break should not exceed pH of 9,5; use low pH non-ionic detergents.
- Do not overdry mats; Basket-temperature of the dryer should not exceed 82 °C.
- If mats are not dried, the final rinse can be increased to 49 °C. This will reduce moisture retention following extraction.
- Lay mats flat following removal from washer; allow mats to cool before rolling.